



### Description

Cable gland with NBR soft rubber seal and IP68 protection rating (10 bar) according to EN 60529. Available in metric thread from M12 to M63 and PG7 to PG48 thread for various cable diameters. Made of self-extinguishing polyamide 6 in grey RAL 7035 and black RAL 9005. Industrial and special applications.

### Advantages

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

Made of self-extinguishing Polyamide 6. V0 fire resistance according to UL 94. Halogen free. Resistant to UV radiation, UL\_f1 classification.

Protection index EN 60529: IP68 with 10 bars of pressure for immersion in water.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C.

### Applications

Its use is recommended in the manufacture of OEM equipment and outdoor, industrial and marine applications.

### Solutions



SECTOR FERROVIARIO



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data

Colour	Black RAL 9005	kg/u	0.009
M/PG	M16	u	50
G (mm)	8	Material	NBR,POLIAMIDA 6
Cable diameter range	5 / 10	IP	IP68
Ø d1 (mm)	14	Working temperature range (°C)	-25 / 90 °C
L (mm)	33	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
Torque wrench	22		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic