




Description

Cable gland with improved diaphragm closure system and NBR seal with an IP68 protection rating (10 bar) according to EN 60529. Available in metric threads from M12 to M63 and in threads PG7 to PG48 for various cable diameters. Manufactured in self-extinguishing polyamide 6 in black (RAL 9005). ATEX for applications in explosive atmospheres.

Advantages

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

ATEX Classification: II 2G 1D.

Made of self-extinguishing Polyamide 6. V0 fire resistance according to UL 94. Halogen free. Resistant to UV radiation, UL_f1 classification.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C. Protection index EN 60529: IP68 with 10 bar pressure for water immersion.

Applications

Its use is recommended for the protection of wiring and conductors with high sealing requirements in ATEX classified installations with risk of fire or explosion, industrial, OEM equipment manufacturing, outdoor, industrial and marine applications.

Solutions



Product data

ETIM 10	EC000441	kg/u	0,072
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		u	10
Colour	Black RAL 9005	Material	NBR,POLIAMIDA 6
M/PG	M40	IP	IP68
G (mm)	13	Working temperature range (°C)	-15 / 90 °C
Cable diameter range	22 / 32	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
Ø d1 (mm)	39		
L (mm)	61		
Torque wrench	53		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

