




Description

Cable gland with improved diaphragm closure system and NBR seal with an IP68 protection rating (10 bar) according to EN 60529. Available in metric threads from M12 to M63 and in threads PG7 to PG48 for various cable diameters. Manufactured in self-extinguishing polyamide 6 in black (RAL 9005). ATEX for applications in explosive atmospheres.

Advantages

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

ATEX Classification: II 2G 1D.

Made of self-extinguishing Polyamide 6. V0 fire resistance according to UL 94. Halogen free. Resistant to UV radiation, UL_f1 classification.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C. Protection index EN 60529: IP68 with 10 bar pressure for water immersion.

Applications

Its use is recommended for the protection of wiring and conductors with high sealing requirements in ATEX classified installations with risk of fire or explosion, industrial, OEM equipment manufacturing, outdoor, industrial and marine applications.

Solutions



Product data			
ETIM 10		EC000441	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Colour		Black RAL 9005	
M/PG		M63	
G (mm)		14	
Cable diameter range		37 / 44	
Ø d1 (mm)		51	
L (mm)		62	
Torque wrench		65	
		kg/u	0,102
		u	5
		Material	NBR,POLIAMIDA 6
		IP	IP68
		Working temperature range (°C)	-15 / 90 °C
		Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic