
Industrial HSK Cable gland

17/11/2026

HSK-K L Cablegland (Ref: 22015201)





Description

Cable gland with improved diaphragm closure system and NBR seal, long thread and IP68 protection rating (10 bar) according to EN 60529. Available in metric threads from M12 to M63 and in PG7 to PG48 threads for various diameters of cable. Made of self-extinguishing polyamide 6 in grey RAL 7035 and black RAL 9005. Industrial and special applications.

Advantages

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

Made of self-extinguishing Polyamide 6. V0 fire resistance according to UL 94. Halogen free. Resistant to UV radiation, UL_f1 classification.

Protection index EN 60529: IP68 with 10 bars of pressure for immersion in water.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C.

Applications

Its use is recommended for the protection of wiring and conductors with high sealing requirements in industrial installations, manufacture of OEM equipment and in industrial and marine applications.

Solutions

RAILWAY APPLICATIONS

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

HSK-K L Cablegland (Ref: 22015201)

Product data

ETIM 10	EC000441
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	
Colour	Grey RAL 7035
M/PG	M20
G (mm)	15
Cable diameter range	10 / 14
Ø d1 (mm)	18
L (mm)	43
Torque wrench	27

kg/u	0,010
u	50
Material	NBR,POLIAMIDA 6
IP	IP68
Working temperature range (°C)	-25 / 90 ºC
Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."