




Description

Cable gland with an improved diaphragm closure system and NBR internal seal, with an IP68 protection rating (10 bar) according to EN 60529. Available in metric thread from M12 to M63 and in thread PG7 to PG48 for different cable diameters. Made of nickel-plated brass. Industrial and special applications.

Advantages

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

Made of nickel-plated brass.

Protection index EN 60529: IP68 with 10 bars of pressure for immersion in water.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C.

Applications

Its use is recommended for the protection of wiring and conductors with high sealing requirements in industrial installations/applications and the manufacturing of OEM equipment.

Solutions



RAILWAY APPLICATIONS



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data			
ETIM 10		EC000441	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Protection System		LTN	
Finish		Nickel-plated brass	
M/PG		M40	
G (mm)		8	
Cable diameter range		22 / 32	
Ø d1 (mm)		39	
L (mm)		45	
Torque wrench		50	
kg/u		0,168	
u		10	
Material		LATÓN NIQUELADO,NBR,POLIAMIDA 6	
IP		IP68	
Working temperature range (°C)		-25 / 90 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic