
Industrial HSK Cable gland

HSK-M Cablegland (Ref: 22051630)





Description

Cable gland with an improved diaphragm closure system and NBR internal seal, with an IP68 protection rating (10 bar) according to EN 60529. Available in metric thread from M12 to M63 and in thread PG7 to PG48 for different cable diameters. Made of nickel-plated brass. Industrial and special applications.

Advantages

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

Made of nickel-plated brass.

Protection index EN 60529: IP68 with 10 bars of pressure for immersion in water.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C.

Applications

Its use is recommended for the protection of wiring and conductors with high sealing requirements in industrial installations/applications and the manufacturing of OEM equipment.

Solutions

RAILWAY APPLICATIONS

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

HSK-M Cablegland (Ref: 22051630)

Product data

ETIM 10	EC000441
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	
Protection System	LTN
Finish	Nickel-plated brass
M/PG	M63
G (mm)	10
Cable diameter range	37 / 44
Ø d1 (mm)	51
L (mm)	48

Torque wrench	64
kg/u	0,365
u	5
Material	LATÓN NIQUELADO,NBR,POLIAMIDA 6
IP	IP68
Working temperature range (°C)	-25 / 90 °C
Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."