
Industrial HSK Cable gland

17/11/2026

HSK-M-EX Cablegland (Ref: 22081400)





Description

Metal cable gland with improved diaphragm closure system with NBR seal and an IP68 protection rating (10 bar) according to EN 60529. Available in metric threads from M12 to M63 and in PG7 to PG48 threads for various cable diameters. Made of nickel-plated brass. For ATEX applications with explosive atmospheres.

Advantages

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

ATEX Classification: II 2G 1D.

Made of nickel-plated brass.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C. Protection index EN 60529: IP68 with 10 bar pressure for water immersion.

Applications

Its use is recommended for the protection of wiring and conductors with high sealing requirements in ATEX classified installations with risk of fire or explosion, industrial, OEM equipment manufacturing, outdoor, industrial and marine applications.

Solutions

OFFSHORE, PORTS

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

HSK-M-EX Cablegland (Ref: 22081400)

Product data

ETIM 10	EC000441
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	
Protection System	LTN
Finish	Nickel-plated brass
M/PG	M40
G (mm)	8
Cable diameter range	22 / 32
Ø d1 (mm)	39
L (mm)	45

Torque wrench	50
kg/u	0,171
u	10
Material	LATÓN NIQUELADO,NBR,POLIAMIDA 6
IP	IP68
Working temperature range (°C)	-15 / 90 °C
Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."