

IRIS-M IA Cablegland



Description

Advantages

Applications

Solutions



Main technical characteristics

 LTN	 NW 5	 PG13, PG16, PG21, M20, M25, M32	1	 LATÓN NIQUELADO,NBR	 IP65	 -25 / 90 °C
 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA			ETIM 10 EC000441			

Product data

					Ref	kg/u	
PG13	6.5	16	29.5	22	21930013	0,032	50
PG16	6.5	18	30.5	24	21930016	0,039	50
PG21	7	22	32	30	21930021	0,061	50
M20	8	16	31	22	21931200	0,043	50
M25	8	18	32	27	21931250	0,058	25
M32	9	22	34	34	21931320	0,102	25

 Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic