Metallic Cable glands

IRIS-M IMC Cablegland



Description

Advantages

Applications

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

IRIS-M IMC Cablegland

Main technical characteristics

LTN | DN NW 3, NW 4, NW 5, NW 6, NW 7, NW 9, NW 8 | PG 9, PG11, M16, PG13, PG16, PG21, M20, M25, M32, PG29, M40

LATÓN NIQUELADO,NBR | IP65 | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA | ETIM 10 EC000441

Product data

DN					L (mm)		REF	kg/u		
NW 3	PG 9	6	11	2	27	17	21230009	0,025	50	-25 / 90 °C
NW 4	PG11	6	14	2	28	20	21230011	0,028	50	-25 / 90 °C
NW 3	M16	7	11	2	28	18	21231160	0,026	50	-25 / 90 °C
NW 5	PG11	6	14	2	28	20	21330011	0,028	50	-25 / 90 °C
NW 6	PG13	6.5	16	2	29.5	22	21330013	0,031	50	-25 / 90 °C
NW 7	PG16	6.5	18	2	30.5	24	21330016	0,039	50	-25 / 90 °C
NW 9	PG21	7	22	2	32	30	21330021	0,060	50	-25 / 90 °C
NW 6	M20	8	16	2	31	22	21331200	0,042	50	-25 / 90 °C
NW 7	M25	8	18	2	32	27	21331250	0,058	25	-25 / 90 °C
NW 9	M32	9	22	2	34	34	21331320	0,101	25	-25 / 90 °C
NW 3	PG 9	6	11	3	27	17	21430009	0,025	50	-25 / 90 °C
NW 7	PG21	7	22	3	32	30	21430021	0,060	50	-25 / 90 °C
NW 9	PG29	8	30	4	39	40	21430029	0,126	25	-25 / 90 °C
NW 3	M16	7	11	3	28	18	21431160	0,026	50	-25 / 90 °C
NW 7	M32	9	22	3	34	34	21431320	0,042	25	-25 / 90 °C
NW 9	M40	9	30	4	40	43	21431400	0,161	10	-25 / 90 °C
NW 5	PG11	6	14	3	28	20	21530011	0,028	50	-25 °C
NW 5	PG13	6.5	16	3	29.5	22	21530013	0,031	50	-25 °C
NW 6	PG16	6.5	18	3	30.5	24	21530016	0,039	50	-25 °C
NW 8	PG21	7	22	3	32	30	21530021	0,060	50	-25 / 90 °C
NW 5	M20	8	16	3	31	22	21531200	0,042	50	-25 / 90 °C
NW 6	M25	8	18	3	32	27	21531250	0,058	25	-25 / 90 °C
NW 8	M32	9	22	3	34	34	21531320	0,101	25	-25 / 90 °C
NW 3	PG 9	6	11	4	27	17	21630009	0,025	50	-25 / 90 °C
NW 5	PG16	6.5	18	4	30.5	24	21630016	0,039	50	-25 / 90 °C
NW 7	PG21	7	22	4	32	30	21630021	0,060	50	-25 / 90 °C
NW 3	M16	7	11	4	28	18	21631160	0,026	50	-25 / 90 °C
NW 5	M25	8	18	4	32	27	21631250	0,058	25	-25 / 90 °C
NW 7	M32	9	22	4	34	34	21631320	0,101	25	-25 / 90 °C
NW 4	PG21	7	22	8	32	30	21830021	0,060	50	-25 / 90 °C
NW 3	PG29	8	30	16	39	40	21830029	0,128	25	-25 / 90 °C
NW 4	M32	9	22	8	34	34	21831320	0,101	25	-25 / 90 °C
NW 3	M40	9	30	16	40	43	21831400	0,163	10	-25 / 90 °C

Protection System

CU - Copper electroplated

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."