



Description
Metal cable gland with diaphragm closure system and multi hole plug for cables, protection index of IP65 according to EN 60529, PG11 to 2 cables NW 4. Manufactured in „.
Advantages
Applications
Solutions

Product data			
Protection System	LTN	Torque wrench	20
Finish	Nickel-plated brass	kg/u	0.028
DN	NW 4	u	50
M/PG	PG11	Material	LATÓN NIQUELADO,NBR
G (mm)	6	IP	IP65
Ø d1 (mm)	14	Working temperature range (°C)	-25 / 90 °C
Holes	2	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
L (mm)	28		

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass
Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic