

IRIS-M IMC Cablegland (Ref: 21330013)

1/2



Description

Metal cable gland with diaphragm closure system and multi hole plug for cables, protection index of IP65 according to EN 60529, PG13 to 2 cables NW 6. Manufactured in „.

Advantages

Applications

Solutions



Product data			
ETIM 10		EC000441	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Protection System		LTN	
Finish		Nickel-plated brass	
DN		NW 6	
M/PG		PG13	
G (mm)		6.5	
Ø d1 (mm)		16	
Holes		2	
L (mm)		29.5	
Torque wrench		22	
kg/u		0,031	
u		50	
Material		LATÓN NIQUELADO,NBR	
IP		IP65	
Working temperature range (°C)		-25 / 90 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic