



Description
Metal cable gland with diaphragm closure system and multi hole plug for cables, protection index of IP65 according to EN 60529, PG21 to 8 cables NW 4. Manufactured in „.
Advantages
Applications
Solutions

Product data			
Protection System	LTN	Torque wrench	30
Finish	Nickel-plated brass	kg/u	0.060
DN	NW 4	u	50
M/PG	PG21	Material	LATÓN NIQUELADO,NBR
G (mm)	7	IP	IP65
Ø d1 (mm)	22	Working temperature range (°C)	-25 / 90 °C
Holes	8	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
L (mm)	32		

 Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic