



Description
Advantages
Applications
Solutions



Main technical characteristics									
LTN	Nickel-plated brass	7, 8, 10, 12, 14	13, 15, 22, 28, 33, 45						
PG16, PG21, PG29, PG36, PG42, PG48, M25, M32, M40, M50, M63	LATÓN NIQUELADO,NBR,POLIAMIDA 6	IP65	-25 / 90 °C						
LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	ETIM EC000441								

Product data									
					L _{mm}		Ref	kg/u	
7	13	PG16	6.5	18	30.5	24	21130016	0.039	50
7	15	PG21	7	22	32	30	21130021	0.060	50
8	22	PG29	8	30	39	40	21130029	0.128	25
10	28	PG36	10	39	47	50	21130036	0.212	10
12	33	PG42	12	45	49	57	21130042	0.247	5
14	45	PG48	14	51	52	64	21130048	0.360	5
7	13	M25	8	18	32	27	21131250	0.058	25
7	15	M32	9	22	34	34	21131320	0.101	25
8	22	M40	9	30	40	43	21131400	0.163	10
10	28	M50	9	39	46	55	21131500	0.296	5
14	45	M63	14	51	52	68	21131630	0.404	5

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester

TPV - Thermoplastic