



Description

Metal cable gland with diaphragm closure system for flat cables, and a protection index of IP65 according to EN 60529, PG21 for cables 7x15 mm. Manufactured in ...

Advantages

Applications

Solutions



| Product data                          |  |                                              |  |
|---------------------------------------|--|----------------------------------------------|--|
| ETIM 10                               |  | EC000441                                     |  |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |  |                                              |  |
| Protection System                     |  | LTN                                          |  |
| Finish                                |  | Nickel-plated brass                          |  |
| Flange (mm)                           |  | 7                                            |  |
| Width (mm)                            |  | 15                                           |  |
| M/PG                                  |  | PG21                                         |  |
| G (mm)                                |  | 7                                            |  |
| Ø d1 (mm)                             |  | 22                                           |  |
| L (mm)                                |  | 32                                           |  |
| Torque wrench                         |  | 30                                           |  |
| kg/u                                  |  | 0,060                                        |  |
| u                                     |  | 50                                           |  |
| Material                              |  | LATÓN NIQUELADO,NBR,POLIAMIDA 6              |  |
| IP                                    |  | IP65                                         |  |
| Working temperature range (°C)        |  | -25 / 90 °C                                  |  |
| Fire resistance                       |  | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA |  |

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic