

IRIS-M IP Cablegland (Ref: 21130029)



Description

Metal cable gland with diaphragm closure system for flat cables, and a protection index of IP65 according to EN 60529, PG29 for cables 8x22 mm. Manufactured in ...

Advantages

Applications

Solutions



Product data

ETIM 10	EC000441	Torque wrench	40
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		kg/u	0,128
Protection System	LTN	u	25
Finish	Nickel-plated brass	Material	LATÓN NIQUELADO,NBR,POLIAMIDA 6
Flange (mm)	8	IP	IP65
Width (mm)	22	Working temperature range (°C)	-25 / 90 °C
M/PG	PG29	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
G (mm)	8		
Ø d1 (mm)	30		
L (mm)	39		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic