



Description
Metal cable gland with diaphragm closure system for flat cables, and a protection index of IP65 according to EN 60529, M50 for cables 10x28 mm. Manufactured in
Advantages
Applications
Solutions

Product data

ETIM 10	EC000441	Torque wrench	55
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		kg/u	0,296
Protection System	LTN	u	5
Finish	Nickel-plated brass	Material	LATÓN NIQUELADO,NBR,POLIAMIDA 6
Flange (mm)	10	IP	IP65
Width (mm)	28	Working temperature range (°C)	-25 / 90 °C
M/PG	M50	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
G (mm)	9		
Ø d1 (mm)	39		
L (mm)	46		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

