



Description

Cable gland with improved diaphragm closure system and TPV seal, head with flexible end for protection of the cable bending and an IP68 protection rating (5 bar) according to EN 60529. Available in metric thread from M12 to M25 and in thread PG7 to PG21 for various cable diameters. Manufactured in self-extinguishing polyamide 6 grey colour RAL 7035 and black RAL 9005. Available with long thread.

Advantages

CE conformity with regard to directive 2014/35 and standard IEC 62444.

It has flexible extension to protect the cable exit, allowing for the correct bending of the cable.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Diaphragm closure system with TPV inner seal.

Working temperature: -20°C to + 100°C. Protection index EN 60529: IP68 with 5 bar pressure for water immersion.

Applications

Its use is recommended for the protection of wiring and conductors with high sealing requirements in general installations, manufacturing of OEM equipment and in industrial applications.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



IRIS-P FLEX Cablegland (Ref: 21059201)

2/2

Product data

Colour	Black RAL 9005	kg/u	0.022
M/PG	M20	u	100
G (mm)	15	Material	POLIAMIDA 6,TPV
Cable diameter range	10 / 14	IP	IP68
Ø d1 (mm)	18	Working temperature range (°C)	-20 / 100 °C
L (mm)	122	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
Torque wrench	27		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic