

IRIS-P IA Cablegland



Description

Advantages

Applications

Solutions



Main technical characteristics							
COLOUR Grey RAL 7035, Black RAL 9005, Grey RAL 7001			DN NW 5	PG13, PG16, PG21, M20, M25	1	50	POLIAMIDA 6,TPV
IP65	-25 / 60 °C	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA			ETIM 10 EC000441		

Product data							
COLOUR				L _{mm}		Ref	kg/u
Grey RAL 7035	PG13	9	16	38	24	21940013	0,012
Grey RAL 7035	PG16	9	18	42	27	21940016	0,015
Grey RAL 7035	PG21	11	22	49	33	21940021	0,025
Grey RAL 7035	M20	10	16	39	24	21941200	0,012
Grey RAL 7035	M25	10	22	48	33	21941250	0,025
Black RAL 9005	PG13	9	16	38	24	21950013	0,012
Black RAL 9005	PG16	9	18	42	27	21950016	0,015
Black RAL 9005	PG21	11	22	49	33	21950021	0,025
Black RAL 9005	M20	10	16	39	24	21951200	0,012
Black RAL 9005	M25	10	22	48	33	21951250	0,025
Grey RAL 7001	PG13	9	16	38	24	21960013	0,012
Grey RAL 7001	PG16	9	18	42	27	21960016	0,015
Grey RAL 7001	PG21	11	22	49	33	21960021	0,025
Grey RAL 7001	M20	10	16	39	24	21961200	0,012
Grey RAL 7001	M25	10	22	48	33	21961250	0,025

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane

IRIS-P IA Cablegland

- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic

