



Description
Cable gland with diaphragm closure system and multi hole plug for 4 cables, protection rating IP65 according to EN 60529, M32 for cables NW 9. Manufactured in colour Grey RAL 7035.
Advantages
Applications
Solutions

Product data			
Colour	Grey RAL 7035	Torque wrench	42
DN	NW 9	kg/u	0.045
M/PG	M32	u	25
G (mm)	10	Material	POLIAMIDA 6,TPV
Ø d1 (mm)	30	IP	IP65
Holes	4	Working temperature range (°C)	-25 / 60 °C
L (mm)	51	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic