



Description

Cable gland with diaphragm closure system and multi hole plug for 3 cables, protection rating IP65 according to EN 60529, M20 for cables NW 6. Manufactured in colour Grey RAL 7035.

Advantages

Applications

Solutions



Product data

ETIM 10	EC000441	Torque wrench	27
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		kg/u	0,012
Colour	Grey RAL 7035	u	50
DN	NW 6	Material	POLIAMIDA 6,TPV
M/PG	M20	IP	IP65
G (mm)	10	Working temperature range (°C)	-25 / 60 °C
Ø d1 (mm)	18	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
Holes	3		
L (mm)	43		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

