



Description

Cable gland with diaphragm closure system and multi hole plug for 8 cables, protection rating IP65 according to EN 60529, PG21 for cables NW 4. Manufactured in in colour Grey RAL 7035.

Advantages

Applications

Solutions



Product data

ETIM 10	EC000441	Torque wrench	33
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		kg/u	0,024
Colour	Grey RAL 7035	u	50
DN	NW 4	Material	POLIAMIDA 6,TPV
M/PG	PG21	IP	IP65
G (mm)	11	Working temperature range (°C)	-25 / 60 °C
Ø d1 (mm)	22	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
Holes	8		
L (mm)	49		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

