



### Description

Cable gland with diaphragm closure system and multi hole plug for 8 cables, protection rating IP65 according to EN 60529, M25 for cables NW 4. Manufactured in colour Grey RAL 7035.

### Advantages

### Applications

### Solutions



| Product data                          |  |                                              |  |
|---------------------------------------|--|----------------------------------------------|--|
| ETIM 10                               |  | EC000441                                     |  |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |  |                                              |  |
| Colour                                |  | Grey RAL 7035                                |  |
| DN                                    |  | NW 4                                         |  |
| M/PG                                  |  | M25                                          |  |
| G (mm)                                |  | 10                                           |  |
| Ø d1 (mm)                             |  | 22                                           |  |
| Holes                                 |  | 8                                            |  |
| L (mm)                                |  | 48                                           |  |
| Torque wrench                         |  | 33                                           |  |
| kg/u                                  |  | 0,024                                        |  |
| u                                     |  | 50                                           |  |
| Material                              |  | POLIAMIDA 6,TPV                              |  |
| IP                                    |  | IP65                                         |  |
| Working temperature range (°C)        |  | -25 / 60 °C                                  |  |
| Fire resistance                       |  | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA |  |

| Protection System                 |
|-----------------------------------|
| CU - Copper electroplated         |
| PG - Pregalvanised                |
| EZ - Electrogalvanised            |
| BC - Electrogalvanised Bichromate |
| BK8 - High Resistance Coating     |
| GC - Hot Dip Galvanising          |
| INOX - Stainless Steel            |
| PT - Polyester Paint              |
| AL - Aluminum                     |
| LN - Brass or Nickel-plated brass |

| Insulating materials                      |
|-------------------------------------------|
| PC+ABS - Halogen Free Polycarbonate + ABS |
| PVC - Polyvinyl Chloride                  |
| PP - Halogen Free Polypropylene           |
| PA6 - Halogen Free Polyamide 6            |
| PA12 - Halogen Free Polyamide 12          |
| PU - Polyurethane                         |
| PE - Polyethylene                         |
| NBR - NBR rubber                          |
| PET - Thermoplastic Polyester             |
| TPV - Thermoplastic                       |