

IRIS-P IP Cablegland



Description

Advantages

Applications

Solutions



IRIS-P IP Cablegland

Main technical characteristics

Colour Grey RAL 7035, Black RAL 9005, Grey RAL 7001	7, 8, 10, 12, 14	13, 15, 22, 28, 33, 45			
PG16, PG21, PG29, PG36, PG42, PG48, M20, M25, M32, M40, M50, M63		POLIAMIDA 6,TPV	IP65	-25 / 60 °C	
LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	ETIM 10 EC000441				

Product data

COLOUR	7	13	PG16	9	18	L _{mm}	27	Ref	kg/u	50
Grey RAL 7035	7	15	PG21	11	22	49	33	21140021	0,024	50
Grey RAL 7035	8	22	PG29	11	30	52	42	21140029	0,044	25
Grey RAL 7035	10	28	PG36	13	39	64	53	21140036	0,074	10
Grey RAL 7035	12	33	PG42	13	45	66	60	21140042	0,090	5
Grey RAL 7035	14	45	PG48	14	51	69	65	21140048	0,103	5
Grey RAL 7035	7	13	M20	10	18	43	27	21141201	0,012	50
Grey RAL 7035	7	15	M25	10	22	48	33	21141250	0,024	50
Grey RAL 7035	8	22	M32	10	30	51	42	21141320	0,047	25
Grey RAL 7035	10	28	M40	10	39	61	53	21141400	0,088	10
Grey RAL 7035	12	33	M50	18	45	71	60	21141500	0,112	5
Grey RAL 7035	14	45	M63	18	51	73	70	21141630	0,154	5
Black RAL 9005	7	13	PG16	9	18	42	27	21150016	0,015	50
Black RAL 9005	7	15	PG21	11	22	49	33	21150021	0,024	50
Black RAL 9005	8	22	PG29	11	30	52	42	21150029	0,044	25
Black RAL 9005	10	28	PG36	13	39	64	53	21150036	0,074	10
Black RAL 9005	12	33	PG42	13	45	66	60	21150042	0,090	5
Black RAL 9005	14	45	PG48	14	51	69	65	21150048	0,103	5
Black RAL 9005	7	13	M20	10	18	43	27	21151201	0,012	50
Black RAL 9005	7	15	M25	10	22	48	33	21151250	0,024	50
Black RAL 9005	8	22	M32	10	30	51	42	21151320	0,047	25
Black RAL 9005	10	28	M40	10	39	61	53	21151400	0,088	10
Black RAL 9005	12	33	M50	18	45	71	60	21151500	0,112	5
Black RAL 9005	14	45	M63	18	51	73	70	21151630	0,154	5
Grey RAL 7001	7	13	PG16	9	18	42	27	21160016	0,015	50
Grey RAL 7001	7	15	PG21	11	22	49	33	21160021	0,024	50
Grey RAL 7001	8	22	PG29	11	30	52	42	21160029	0,044	25
Grey RAL 7001	10	28	PG36	13	39	64	53	21160036	0,074	10
Grey RAL 7001	12	33	PG42	13	45	66	60	21160042	0,090	5
Grey RAL 7001	14	45	PG48	14	51	69	65	21160048	0,103	5
Grey RAL 7001	7	13	M20	10	18	43	27	21161201	0,012	50
Grey RAL 7001	7	15	M25	10	22	48	33	21161250	0,024	50
Grey RAL 7001	8	22	M32	10	30	51	42	21161320	0,047	25



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



COLOUR									Ref	kg/u	
Grey RAL 7001	10	28	M40	10	39	61	53		21161400	0,088	10
Grey RAL 7001	12	33	M50	18	45	71	60		21161500	0,112	5
Grey RAL 7001	14	45	M63	18	51	73	70		21161630	0,154	5

 Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic