



### Description

Metal reducer for metric thread. Available in different sizes. Made of nickel-plated brass.

### Advantages

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of nickel-plated brass.

Protection Index EN 60529: IP54 / IP68 (with O-ring).

### Applications

Suitable for the reduction of metric threads in cable glands and conduit fittings for the protection and management of wiring in general and industrial applications.

### Solutions



## Product data

|                                       |                     |                                |                                              |
|---------------------------------------|---------------------|--------------------------------|----------------------------------------------|
| ETIM 10                               | EC000938            | L (mm)                         | 9                                            |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |                     | kg/u                           | 0,011                                        |
| Protection System                     | LTN                 | u                              | 100                                          |
| Finish                                | Nickel-plated brass | Material                       | Nickel-plated brass                          |
| M/PG                                  | PG13                | Working temperature range (°C) | -45 / 150 °C                                 |
| G (mm)                                | 6.5                 | Fire resistance                | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA |
| M/PG 2                                | PG 9                |                                |                                              |
| Ø d2 (mm)                             | 22                  |                                |                                              |

## Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

