



Description

Advantages

Applications

Solutions



Product data			
ETIM 10		EC000940	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		u	5
Protection System		LTN	
Finish		Nickel-plated brass	
M/PG		M50	
G (mm)		5.6	
Torque wrench		55	
		kg/u	0,028
		Material	Nickel-plated brass
		Working temperature range (°C)	-60 / 200 °C
		Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic