



#### Description

Metal nut with PG42 thread for connecting conduits, connectors and metal cable glands. Finished in .

#### Advantages

#### Applications

#### Solutions



Product data

Protection System	INOX	kg/u	0.033
Finish	Stainless Steel AISI 303	u	5
M/PG	PG42	Material	Stainless steel AISI 303
G (mm)	5	Working temperature range (°C)	-60 / 200 °C
Torque wrench	60	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic