
Nuts Accessories 30/04/2024

TCP Nut (Ref: 40024048)











1/2



Description

Halogen-free polyamide 6 nut, PG48 for connection of fittings and threaded items for plastic rigid, corrugated and flexible conduit systems, in colour Black RAL 9005.

Advantages

Compatible with metric or PG plastic threaded fittings for all ranges of rigid, flexible and corrugated conduits.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Available in Grey RAL 7035, dark grey RAL 7001 and black RAL 9005.

 $Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 \ y \ UNE/EN 60754-1 \ and \ flame-retardant.$

Working temperature: -25°C to + 105°C.

Applications

Suitable for connection of threaded fittings of all ranges of rigid and flexible plastic conduits for the conduction of electric cables in building and industrial applications.

Solutions













30/04/2024 **Nuts Accessories**

TCP Nut (Ref: 40024048)

2/2

Р	ro	αι	ιςτ	a	aτ	a

Colour	Black RAL 9005	u	25	
M/PG	PG48	Material	Poyamide 6	
G (mm)	8	Working temperature range (°C)	-25 / 105 °C	
Torque wrench	70	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	
kg/u	0.014	riie resistante		

S Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

M Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic









