


Description

Halogen-free polyamide 6 nut, PG 7 for connection of fittings and threaded items for plastic rigid, corrugated and flexible conduit systems, in colour Grey RAL 7001.

Advantages

Compatible with metric or PG plastic threaded fittings for all ranges of rigid, flexible and corrugated conduits.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Available in Grey RAL 7035, dark grey RAL 7001 and black RAL 9005.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Working temperature: -25°C to + 105°C.

Applications

Suitable for connection of threaded fittings of all ranges of rigid and flexible plastic conduits for the conduction of electric cables in building and industrial applications.

Solutions



Product data

ETIM 10	EC000940	u	100
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		Material	Polyamide 6
Colour	Grey RAL 7001	Working temperature range (°C)	-25 / 105 °C
M/PG	PG 7	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
G (mm)	5		
Torque wrench	19		
kg/u	0,001		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

