


## Pemsaband RX. Reinforced Cable tray

1/4



### Description

Perforated and reinforced sheet steel tray of 60 and 100 mm height, in GC or PG Protection System with a safety edge. The Pemsaband® RX tray, with a gauge of 1.5 mm, is suitable for supporting and routing electrical cables of high loads. There are a wide variety of sizes to choose from according to the needs of each installation.

### Advantages

Sheet thickness of 1.5 mm gives greater strength and load capacity.

Profiled safety edge for cable protection. It also prevents possible cuts when handled by the installer.

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

E90 fire resistance (90 minutes, 1000°C) according to DIN 4102-12.

Wide variety of sizes, protection systems and accessories to adapt to the requirements of each electrical installation.

### Applications

Support, management and distribution of cables in Electrical and/or telecommunications installations in: Civil Works, Tunnels, Car Parks, Public Buildings, Shopping Centres, Data Processing Centres, Infrastructures, Airports, Underground and Railway. Tertiary sector and industrial applications: Naval, Petrochemical, Textile, Chemical and Food. Indoor applications in the dry or in exterior atmospheres with wet environments according to the various protection systems.

### Solutions



OFFSHORE, PORTS TUNNELS INFRASTRUCTURES FIRE RESISTANCE SOLUTION



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



|                                                                                               |                                                                                                                |                                                                                     |                                                                                     |                                                                                                              |                                                                                          |                                                                                                         |                                                                                          |
|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
|  60, 100      |  100, 200, 300, 400, 500, 600 |  3 |  6 |  Steel with surface coating |  20 J |  e <sub>mm</sub> 1.5 |  IP23 |
|  -50 / 150 °C | ETIM 10<br>EC000047                                                                                            |                                                                                     |                                                                                     |                                                                                                              |                                                                                          |                                                                                                         |                                                                                          |

| Ⓢ  | Class EC 61537 |  |  | Ref      | kg/u  | mm²   |  |
|----|----------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|----------|-------|-------|-------------------------------------------------------------------------------------|
| PG | Class 3        | 60                                                                                | 100                                                                               | 76122100 | 2,470 | 5358  | E90 (90 min. 1000°C)                                                                |
| PG | Class 3        | 60                                                                                | 200                                                                               | 76122200 | 3,431 | 11158 | E90 (90 min. 1000°C)                                                                |
| PG | Class 3        | 60                                                                                | 300                                                                               | 76122300 | 4,701 | 16958 | E90 (90 min. 1000°C)                                                                |
| PG | Class 3        | 60                                                                                | 400                                                                               | 76122400 | 6,002 | 22758 | E90 (90 min. 1000°C)                                                                |
| PG | Class 3        | 60                                                                                | 500                                                                               | 76122500 | 7,082 | 28558 | A1 No combustible                                                                   |
| PG | Class 3        | 60                                                                                | 600                                                                               | 76122600 | 8,212 | 34358 | A1 No combustible                                                                   |
| PG | Class 3        | 100                                                                               | 100                                                                               | 76124100 | 3,371 | 7318  | E90 (90 min. 1000°C)                                                                |
| PG | Class 3        | 100                                                                               | 200                                                                               | 76124200 | 4,331 | 18998 | E90 (90 min. 1000°C)                                                                |
| PG | Class 3        | 100                                                                               | 300                                                                               | 76124300 | 5,511 | 28798 | E90 (90 min. 1000°C)                                                                |
| PG | Class 3        | 100                                                                               | 400                                                                               | 76124400 | 6,802 | 38598 | E90 (90 min. 1000°C)                                                                |
| PG | Class 3        | 100                                                                               | 500                                                                               | 76124500 | 7,872 | 48398 | A1 No combustible                                                                   |
| PG | Class 3        | 100                                                                               | 600                                                                               | 76124600 | 8,992 | 58198 | A1 No combustible                                                                   |
| GC | Class 8        | 60                                                                                | 100                                                                               | 76132100 | 2,700 | 5358  | E90 (90 min. 1000°C)                                                                |
| GC | Class 8        | 60                                                                                | 200                                                                               | 76132200 | 3,751 | 11158 | E90 (90 min. 1000°C)                                                                |
| GC | Class 8        | 60                                                                                | 300                                                                               | 76132300 | 5,131 | 16958 | E90 (90 min. 1000°C)                                                                |
| GC | Class 8        | 60                                                                                | 400                                                                               | 76132400 | 6,552 | 22758 | E90 (90 min. 1000°C)                                                                |
| GC | Class 8        | 60                                                                                | 500                                                                               | 76132500 | 7,732 | 28558 | A1 No combustible                                                                   |
| GC | Class 8        | 60                                                                                | 600                                                                               | 76132600 | 8,972 | 34358 | A1 No combustible                                                                   |
| GC | Class 8        | 100                                                                               | 100                                                                               | 76134100 | 3,741 | 7318  | E90 (90 min. 1000°C)                                                                |
| GC | Class 8        | 100                                                                               | 200                                                                               | 76134200 | 4,801 | 18998 | E90 (90 min. 1000°C)                                                                |
| GC | Class 8        | 100                                                                               | 300                                                                               | 76134300 | 6,101 | 28798 | E90 (90 min. 1000°C)                                                                |
| GC | Class 8        | 100                                                                               | 400                                                                               | 76134400 | 7,522 | 38598 | E90 (90 min. 1000°C)                                                                |
| GC | Class 8        | 100                                                                               | 500                                                                               | 76134500 | 8,702 | 48398 | A1 No combustible                                                                   |
| GC | Class 8        | 100                                                                               | 600                                                                               | 76134600 | 9,942 | 58198 | A1 No combustible                                                                   |

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

### BK8 - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Reijband, Pemsaband, Inducanal, Reijtech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

## Pemsaband **RX**. Reinforced Cable **tray**

LN - Brass or Nickel-plated brass

### Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic




# **Pemsaband RX. Reinforced Cable tray**

4/4

## Load diagrams

□ □ □

## Product applications



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."