

Pemsaband RX. Reinforced Cable tray





Description

Perforated and reinforced sheet steel tray of 60 and 100 mm height, in GC or PG Protection System with a safety edge. The Pemsaband® RX tray, with a gauge of 1.5 mm, is suitable for supporting and routing electrical cables of high loads. There are a wide variety of sizes to choose from according to the needs of each installation.

Advantages

Sheet thickness of 1.5 mm gives greater strength and load capacity.

Profiled safety edge for cable protection. It also prevents possible cuts when handled by the installer.

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

E90 fire resistance (90 minutes, 1000°C) according to DIN 4102-12.

Wide variety of sizes, protection systems and accessories to adapt to the requirements of each electrical installation.

Applications

Support, management and distribution of cables in Electrical and/or telecommunications installations in: Civil Works, Tunnels, Car Parks, Public Buildings, Shopping Centres, Data Processing Centres, Infrastructures, Airports, Underground and Railway. Tertiary sector and industrial applications: Naval, Petrochemical, Textile, Chemical and Food. Indoor applications in the dry or in exterior atmospheres with wet environments according to the various protection systems.

Solutions

OFFSHORE, PORTS TUNNELS INFRASTRUCTURES FIRE RESISTANCE SOLUTION

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Pemsaband RX. Reinforced Cable tray

Main technical characteristics

60, 100 | 100, 200, 300, 400, 500, 600 | 3 | 6 | Steel with surface coating | 20 J | $e_{(mm)}$ 1.5 | IP23 | -50 / 150 °C | A1 No combustible | ETIM 10 EC000047

Product data

Ⓢ	Class IEC 61537			REF	kg/u	mm²
PG	Class 3	60	100	76122100	2,470	5358
PG	Class 3	60	200	76122200	3,431	11158
PG	Class 3	60	300	76122300	4,701	16958
PG	Class 3	60	400	76122400	6,002	22758
PG	Class 3	60	500	76122500	7,082	28558
PG	Class 3	60	600	76122600	8,212	34358
PG	Class 3	100	100	76124100	3,371	7318
PG	Class 3	100	200	76124200	4,331	18998
PG	Class 3	100	300	76124300	5,511	28798
PG	Class 3	100	400	76124400	6,802	38598
PG	Class 3	100	500	76124500	7,872	48398
PG	Class 3	100	600	76124600	8,992	58198
GC	Class 8	60	100	76132100	2,700	5358
GC	Class 8	60	200	76132200	3,751	11158
GC	Class 8	60	300	76132300	5,131	16958
GC	Class 8	60	400	76132400	6,552	22758
GC	Class 8	60	500	76132500	7,732	28558
GC	Class 8	60	600	76132600	8,972	34358
GC	Class 8	100	100	76134100	3,741	7318
GC	Class 8	100	200	76134200	4,801	18998
GC	Class 8	100	300	76134300	6,101	28798
GC	Class 8	100	400	76134400	7,522	38598
GC	Class 8	100	500	76134500	8,702	48398
GC	Class 8	100	600	76134600	9,942	58198

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester


TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Pemsaband RX. Reinforced Cable tray

Load diagrams

Product applications



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."