


### Description

Metal cover used as end closure for the range of Pemsaband® One trays ensuring product tightness and a professional finish. Of 60 mm height, Width 200 mm, With INOX protection system, I304 finish. Quick connection assembly using the Click system without couplers. Made of steel in various sizes and Protection Systems.

### Advantages

Safer professional finish.

Available in all sizes and protection systems: PG, GC and stainless steel AISI304 and AISI316.

Its unique design allows the closure of the various Pemsaband® One perforated trays.

Using this part in the end of the tray provides the closure of the assembly.

### Applications

It is used as the closing end of the system of Pemsaband® One perforated and solid trays to improve the sealing and protection of the installation. Applicable in the management of cables in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial installations, tertiary sector.

### Solutions



## Product data

|                                              |                          |                                       |                          |
|----------------------------------------------|--------------------------|---------------------------------------|--------------------------|
| <b>ETIM 10</b>                               | EC001574                 | <b>u</b>                              | 1                        |
| <b>Huella de CO2. GWP A1-A3 (kg CO2 eq.)</b> | 1,186                    | <b>Material</b>                       | Stainless steel AISI 304 |
| <b>Protection System</b>                     | INOX                     | <b>IP</b>                             | IP44                     |
| <b>Finish</b>                                | Stainless Steel AISI 304 | <b>Working temperature range (°C)</b> | -50 / 150 °C             |
| <b>Resistance Class</b>                      | Class 9C                 | <b>Fire resistance</b>                | A1 No combustible        |
| <b>Flange (mm)</b>                           | 60                       |                                       |                          |
| <b>Width (mm)</b>                            | 200                      |                                       |                          |
| <b>kg/u</b>                                  | 0,223                    |                                       |                          |

## Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



Product applications

□ □ □ □ □ □

