

Stand off bracket Pemsaband Vulcan



Description

Advantages

Applications

Solutions



RENEWABLE ENERGIES



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics					
 PG3, Pregalvanised, HDG, Hot Dip Galvanised	 180, 350	 10	 Steel with surface coating	 100	 -50 / 150 °C
 A1 No combustible					

Product data					
				Ref	kg/u
PG	PG3, Pregalvanised	Class 3	180	67030539	0,217
PG	PG3, Pregalvanised	Class 3	350	67030540	0,337
GC	HDG, Hot Dip Galvanised	Class 6	180	67030541	0,224
GC	HDG, Hot Dip Galvanised	Class 6	350	67030542	0,348

 Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

 Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic