Pemsaband Vulcan Brackets

17/11/2026

Stand off bracket Pemsaband Vulcan



Description

Divider accessory with snap-on mounting system for Pemsaband® Vulcan cable trays. Made of steel, it allows the physical and electromagnetic separation of different cable circuits in the tray. It allows for the physical and electromagnetic separation of different cable circuits within the cable tray..

Advantages

Quick and secure snap-on mounting system without the need for additional tools, saving material and labour costs. Reduces installation time.

Allows physical separation of cables of different nature or voltage, facilitating separation and regulatory compliance of the installation.

Aesthetics integrated with the rest of the Pemsaband®Vulcan range for a professional finish to the installation.

High corrosion resistance. Available in PG and AZ+ protection systems. Class 3 and Class 8 according to BS EN 61537

Regulatory compliance: designed and developed in accordance with edition 3 of IEC 61537, Directive 2014/35/EU (CE marking) and UKCA marking, ensuring safety and reliability in electrical installations.

Applications

Accessory designed for the separation of circuits in the routing of cables in electrical installations. It is applicable to buildings (DCs), infrastructure (tunnels, airports) and the industrial sector. Suitable for indoor and outdoor installation.

Solutions

RENEWABLE ENERGIES

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Stand off bracket Pemsaband Vulcan

Main technical characteristics

PG3, Pregalvanised, HDG, Hot Dip Galvanised | 180, 350 | 10 | Steel with surface coating | 100 | -50 / 150 °C

A1 No combustible | ETIM 10 EC000022

Product data

Ⓢ	Ⓕ	Class IEC 61537		REF	kg/u
PG	PG3, Pregalvanised	Class 3	180	67030539	0,217
PG	PG3, Pregalvanised	Class 3	350	67030540	0,337
GC	HDG, Hot Dip Galvanised	Class 6	180	67030541	0,224
GC	HDG, Hot Dip Galvanised	Class 6	350	67030542	0,348

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."