

Earth Continuity Connector Pemsaband Vulcan



Description

Advantages

Applications

Solutions



Earth Continuity Connector Pemsaband

Vulcan

Main technical characteristics

|                                                                                     |                                                                                         |                                                                                      |                                                                                         |                                                                                                |                                                                                                     |         |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------|
|  LTN |  Brass |  10 |  Brass |  -50 / 150 °C |  A1 No combustible | ETIM 10 |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------|

Product data

| Ømm | Ref      | kg/u  |
|-----|----------|-------|
| 12  | 68000036 | 0,014 |
| 16  | 68000037 | 0,020 |

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

