

Cantilever Arm 41x41 Pemsaband

Vulcan



Description

Advantages

Applications

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Cantilever Arm 41x41 Pemsa**band**

Vulcan

Main technical characteristics

 HDG, Hot Dip Galvanised, EZ3, Electrogalvanised	 500, 600	 1	 Steel with surface coating	 -25 / 105 °C
 E90 (90 min. 1000°C)	ETIM 10			

Product data

				Ref	kg/u	
GC	HDG, Hot Dip Galvanised	Class 6	500	82002610	1,710	165
GC	HDG, Hot Dip Galvanised	Class 6	600	82002611	1,980	141
EZ	EZ3, Electrogalvanised	Class 3	500	83001930	1,690	

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic