

Cantilever Arm 41x41 Pemsa**band**

Vulcan



Description

Advantages

Applications

Solutions



Cantilever Arm 41x41 Pemsa**band**

Vulcan

Main technical characteristics

 HDG, Hot Dip Galvanised, EZ3, Electrogalvanised	 500, 600	 1	 Steel with surface coating	 -25 / 105 °C
 A1 No combustible	ETIM 10			

Product data

				Ref	kg/u	
GC	HDG, Hot Dip Galvanised	Class 6	500	82002610	1,710	165
GC	HDG, Hot Dip Galvanised	Class 6	600	82002611	1,980	141
EZ	EZ3, Electrogalvanised	Class 3	500	83001930	1,690	

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

