

Cover Pemsaband Vulcan



Description

Advantages

Applications

Solutions



Main technical characteristics

PG3, Pregalvanised, ZM High Resistance Alloy

50, 75, 100, 150, 225, 300, 450, 600, 750, 900

Steel with surface coating

IP23

-50 / 150 °C

A1 No combustible

ETIM 10

Product data

§	Ⓕ	Class EC 61537	Ⓚ	Ⓜ	Ref
PG	PG3, Pregalvanised	Class 3	50	3	82004983
PG	PG3, Pregalvanised	Class 3	75	3	82004984
PG	PG3, Pregalvanised	Class 3	100	3	82004985
PG	PG3, Pregalvanised	Class 3	150	3	82004986
PG	PG3, Pregalvanised	Class 3	225	3	82004987
PG	PG3, Pregalvanised	Class 3	300	3	82004988
PG	PG3, Pregalvanised	Class 3	450	3	82004989
PG	PG3, Pregalvanised	Class 3	600	3	82004990
PG	PG3, Pregalvanised	Class 3	750	2	82004991
PG	PG3, Pregalvanised	Class 3	900	2	82004992
AZ+	ZM High Resistance Alloy	Class 8	50	3	82005325
AZ+	ZM High Resistance Alloy	Class 8	75	3	82005326
AZ+	ZM High Resistance Alloy	Class 8	100	3	82005327
AZ+	ZM High Resistance Alloy	Class 8	150	3	82005328
AZ+	ZM High Resistance Alloy	Class 8	225	3	82005329
AZ+	ZM High Resistance Alloy	Class 8	300	3	82005330
AZ+	ZM High Resistance Alloy	Class 8	450	3	82005331
AZ+	ZM High Resistance Alloy	Class 8	600	3	82005332
AZ+	ZM High Resistance Alloy	Class 8	750	2	82005333
AZ+	ZM High Resistance Alloy	Class 8	900	2	82005334

§ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

Cover Pemsaband Vulcan

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

