



- Description
- Advantages
- Applications
- Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data			
ETIM 10		Material	
		Steel with surface coating	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		IP	
		IP23	
Protection System		Working temperature range (°C)	
PG		-50 / 150 °C	
Finish		Fire resistance	
PG3, Pregalvanised		A1 No combustible	
Resistance Class			
Class 3			
Width (mm)			
225			
Length (m)			
3			

Protection System

CU

Copper electroplated

PG

Pregalvanised

EZ

Electrogalvanised

BC

Electrogalvanised Bichromate

BK8

High Resistance Coating

GC

Hot Dip Galvanising

INOX

Stainless Steel

PT

Polyester Paint

AL

Aluminum

LN

Brass or Nickel-plated brass

Insulating materials

PC+ABS

Halogen Free Polycarbonate + ABS

PVC

Polyvinyl Chloride

PP

Halogen Free Polypropylene

PA6

Halogen Free Polyamide 6

PA12

Halogen Free Polyamide 12

PU

Polyurethane

PE

Polyethylene

NBR

NBR rubber

PET

Thermoplastic Polyester

TPV

Thermoplastic