
06/05/2024 Assembly Accessories

Flat Ring (Ref: 39092112)









Description

Flat ring of NBR elastomer in blue colour, metric and PG thread for use with external threaded fittings and cable glands to provide an IP67 protection index to the joint. Available in various sizes.

Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Available in blue.

Available in metric thread: M12, M16, M20, M25, M32, M40 M50 and M63 and PG thread: 7, 9, 11, 13.5, 16, 21, 29, 36 and 48.

Manufactured in NBR elastomer.

Improves the seal of the fitting or cable gland on the box, reaching IP67.

Applications

Suitable for use on an external thread to improve the tightness of the joint with the boxes. Can be used for any range of fittings, conduits or cable glands.

Solutions













06/05/2024 Assembly Accessories

Flat Ring (Ref: 39092112)

2/2

Product data

Colour	Blue RAL 5024	Material	NBR
M/PG	M12	IP	IP67
kg/u	0.000	Working temperature range (°C)	-25 / 105 °C
u	50	Fire resistance	Flame retardant

S Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

® Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic











