

Flat Ring (Ref: 39092125)





Description

Flat ring of NBR elastomer in blue colour, metric and PG thread for use with external threaded fittings and cable glands to provide an IP67 protection index to the joint. Available in various sizes.

Advantages

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Available in blue.

Available in metric thread: M12, M16, M20, M25, M32, M40 M50 and M63 and PG thread: 7, 9, 11, 13.5, 16, 21, 29, 36 and 48.

Manufactured in NBR elastomer.

Improves the seal of the fitting or cable gland on the box, reaching IP67.

Applications

Suitable for use on an external thread to improve the tightness of the joint with the boxes. Can be used for any range of fittings, conduits or cable glands.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Flat Ring (Ref: 39092125)

Product data

ETIM 10	EC001181	**Material**	NBR
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		**IP**	IP67
Colour	Blue RAL 5024	**Working temperature range (°C)**	-25 / 105 °C
M/PG	M25	**Fire resistance**	Flame retardant
kg/u	0,001		
u	50		

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."