

PA6 RA 90° Connector (Ref: 32043416)

1/2



Description

Connector of 90° with external thread in. for DN17 mm, conduit with IP54 protection rating, Fabriqué en POLIAMIDA 6, PG16, PG16, LIBRE DE HALÓGENOS, NO PROPAGADOR DE LA LLAMA, Colour NEGRO RAL 9005. The PA6 connector is suitable for the installation of Pemsaflex®, LG-PA, ST-PA, RB-PA and RB-PU flexible conduits. Self-extinguishing and

Advantages

CE certified in compliance with the low voltage directive 2014/35 / EU

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Protection index EN 60529: IP54.

Click connection system that allows easy and fast coupling to the conduit.

Working temperature: -40°C to + 120°C.

Applications

Suitable for the connection of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots , vehicles and special facilities.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Product data			
ETIM 10		EC001176	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Colour		Black RAL 9005	
DN		NW17	
M/PG		PG16	
G (mm)		13	
Ø d1 (mm)		16.6	
Ø d2 (mm)		32	
Angle		90	
L (mm)		51.5	
A (mm)		51	
kg/u		0,022	
u		40	
Material		Polyamide 6	
IP		IP54	
Working temperature range (°C)		-40 / 120 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic