

RMH Female Connector**Description**

Nickel-plated brass connector with internal thread and polyethylene inner sleeve for the assembly of TM, Ecoflex®, TM-PVC conduits. IP54 protection index. Available in various sizes and in metric threads.

Advantages

It has an internal female thread to allow the connection of RM external threads for joining lengths of flexible conduits.

Protection index EN 60529: IP54.

Working temperature: -25°C to + 90°C.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of nickel-plated brass with a polypropylene inner sleeve.

Applications

Suitable for the connection of TM, TM-PVC and Ecoflex® metallic flexible conduits, in the management of electrical cables for building, tertiary and industrial applications.

Solutions

Main technical characteristics

LTN	Nickel-plated brass	DN NW 7, NW 9, NW11, NW13, NW16, NW21, NW29, NW36, NW48			
M12, M16, M20, M25, M32, M40, M50, M63	LATÓN NIQUELADO,POLIPROPILENO	IP54	-25 / 90 °C		
LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	ETIM 10 EC001180				

Product data

DN				L _{mm}		Ref	kg/u	
NW 7	M12	6	7.5	24	18	37041120	0,014	100
NW 9	M16	7	9.3	27	20	37041160	0,019	100
NW11	M20	7.5	12.1	28.6	24	37041200	0,026	100
NW13	M20	8	13.6	29.1	26	37041201	0,030	50
NW16	M25	9	15.5	32.8	28	37041250	0,032	50
NW21	M32	9	20.2	35	34	37041320	0,052	25
NW29	M40	9	26.7	39.3	45	37041400	0,089	20
NW36	M50	10	34.8	40	56	37041500	0,179	10
NW48	M63	15	45	48.8	70	37041630	0,329	5

Protection System

CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic