
RMM Connector



Description

Metal connector with external thread and nickel-plated brass inner sleeve for the assembly of TM, Ecoflex® and TM-PVC conduits. IP54 protection index. Available ir various sizes and in metric threads.

Advantages

The inner metal bush provides electrical continuity of the installation.

Protection index EN 60529: IP54.

Working temperature: -25°C to + 150°C.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of nickel-plated brass.

Applications

Suitable for the connection of TM, TM-PVC and Ecoflex® metallic flexible conduits, in the management of electrical cables for building, tertiary and industrial applications.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics

LTN | Nickel-plated brass | DN NW 7, NW 9, NW11, NW13, NW16, NW21, NW29, NW36, NW48

PG 7, PG 9, PG11, PG13, PG16, PG21, PG29, PG36, PG48, M12, M16, M20, M25, M32, M40, M50, M63 | Nickel-plated brass | IP54

-45 / 150 °C | A1 No combustible | ETIM 10 EC001180

Product data

DN				$L_{(mm)}$		REF	kg/u	
NW 7	PG 7	5	8	21.5	18	37025007	0,016	100
NW 9	PG 9	6	9.8	22	20	37025009	0,023	100
NW11	PG11	6.5	12.7	22.5	24	37025011	0,032	100
NW13	PG13	6	14.5	23	26	37025013	0,035	50
NW16	PG16	8.5	16.2	26	28	37025016	0,043	50
NW21	PG21	8	21	28	34	37025021	0,066	25
NW29	PG29	9.5	28.6	31	45	37025029	0,133	20
NW36	PG36	10	37.5	38	56	37025036	0,261	10
NW48	PG48	15	48.8	50	70	37025048	0,467	5
NW 7	M12	5	8	21.5	18	37026120	0,016	100
NW 9	M16	6	9.8	22	20	37026160	0,023	100
NW11	M20	6.5	12.7	22.5	24	37026200	0,032	100
NW13	M20	7	14.5	23	26	37026201	0,036	50
NW16	M25	8	16.2	26	28	37026250	0,043	50
NW21	M32	8	21	28	34	37026320	0,066	25
NW29	M40	8	28.6	31	45	37026400	0,130	20
NW36	M50	9	37.5	38	56	37026500	0,255	10
NW48	M63	14	48.8	50	70	37026630	0,457	5

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."