



Description

Metal connector with external thread and nickel-plated brass inner sleeve for the assembly of TM, Ecoflex® and TM-PVC conduits. IP54 protection index. Available in various sizes and in metric threads.

Advantages

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

The inner metal bush provides electrical continuity of the installation.

Made of nickel-plated brass.

Protection index EN 60529: IP54.

Working temperature: -25°C to + 150°C.

Applications

Suitable for the connection of TM, TM-PVC and Ecoflex® metallic flexible conduits, in the management of electrical cables for building, tertiary and industrial applications.

Solutions



Product data			
ETIM 10		EC001180	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Protection System		LTN	
Finish		Nickel-plated brass	
DN		NW16	
M/PG		M25	
G (mm)		8	
Ø d1 (mm)		16.2	
L (mm)		26	
Torque wrench		28	
kg/u		0,043	
u		50	
Material		Nickel-plated brass	
IP		IP54	
Working temperature range (°C)		-45 / 150 °C	
Fire resistance		A1 No combustible	

Protection System

CU

PG

EZ

BC

BK8

GC

INOX

PT

AL

LN

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS

PVC

PP

PA6

PA12

PU

PE

NBR

PET

TPV

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic