RREM Connector

Description

Straight connector in self-extinguishing polyamide 6 in grey RAL 7011 or black RAL 9005 with metric and PG metal thread, halogen-free, flame retardant, IP67 protection rating. The RREM connector is suitable for the installation of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU flexible conduits.

Advantages

Manufactured in polyamide 6. Self-extinguishing, halogen-free and flame-retardant. Metal thread in nickel-plated brass.

Click connection system that allows easy and fast coupling to the conduit.

Suitable for conduit assemblies that need to be connected to equipment or machines with a metal thread. Maintains the electrical continuity of the installation.

Working temperature: -25°C to + 105°C. Degree of protection IP67 according to classification EN60529.

UL, CSA and DNV certification. CE conformance with the 2014/35 directive and the IEC 61386 standard. Halogen-free according to EN 50267-2-1 standard. In accordance with standard EN 60204-1 (machine safety).

Applications

Suitable for the connection of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots , vehicles and special facilities.

Solutions

RAILWAY APPLICATIONS

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

RREM Connector

Main technical characteristics

LTN | Nickel-plated brass | Colour Grey RAL 7011, Black RAL 9005 | DN NW10, NW12, NW17, NW23, NW29, NW36, NW48

M16, M20, M25, M32, M40, M50, M63 | LATÓN NIQUELADO,POLIAMIDA 6 | IP67 | -25 / 105 °C

LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA | ETIM 10 EC001176

Product data

Colour	DN			Od1	Od2	L(mm)		Ref	kg/u	
Grey RAL 7011	NW10	M16	12	10.8	21.1	37.5	19	31102116	0,011	30
Grey RAL 7011	NW12	M20	12	10.6	25	39	22	31102220	0,017	30
Grey RAL 7011	NW17	M25	14	17.7	32	43.5	27	31102425	0,024	30
Grey RAL 7011	NW23	M32	14	24.6	40	52.5	36	31102532	0,042	30
Grey RAL 7011	NW29	M40	14	29	46.5	53.5	41	31102640	0,062	20
Grey RAL 7011	NW36	M50	18	35.7	60.5	64.5	50	31102750	0,117	10
Grey RAL 7011	NW48	M63	15.5	46	73	69	65	31102848	0,156	10
Black RAL 9005	NW10	M16	12	10.8	21.1	37.5	19	32102116	0,011	30
Black RAL 9005	NW12	M20	12	10.6	25	39	22	32102220	0,017	30
Black RAL 9005	NW17	M25	14	17.7	32	43.5	27	32102425	0,024	30
Black RAL 9005	NW23	M32	14	24.6	40	52.5	36	32102532	0,042	30
Black RAL 9005	NW29	M40	14	29	46.5	53.5	41	32102640	0,062	20
Black RAL 9005	NW36	M50	18	35.7	60.5	64.5	50	32102750	0,117	10
Black RAL 9005	NW48	M63	15.5	46	73	69	65	32102863	0,156	10

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

RREM Connector

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."