



Description

Straight connector in self-extinguishing polyamide 6 in grey RAL 7011 or black RAL 9005 with metric and PG metal thread, halogen-free, flame retardant, IP67 protection rating. The RREM connector is suitable for the installation of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU flexible conduits.

Advantages

Suitable for conduit assemblies that need to be connected to equipment or machines with a metal thread. Maintains the electrical continuity of the installation.

UL, CSA and DNV certification. CE conformance with the 2014/35 directive and the IEC 61386 standard. Halogen-free according to EN 50267-2-1 standard. In accordance with standard EN 60204-1 (machine safety).

Manufactured in polyamide 6. Self-extinguishing, halogen-free and flame-retardant. Metal thread in nickel-plated brass.

Click connection system that allows easy and fast coupling to the conduit.

Working temperature: -25°C to + 105°C. Degree of protection IP67 according to classification EN60529.

Applications

Suitable for the connection of Pemsaflex®, LG-PA, ST-PA, RF-PA, RB-PA and RB-PU conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots , vehicles and special facilities.

Solutions



RAILWAY APPLICATIONS



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Product data			
ETIM 10		EC001176	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Protection System		LTN	
Finish		Nickel-plated brass	
Colour		Grey RAL 7011	
DN		NW36	
M/PG		M50	
G (mm)		18	
Ø d1 (mm)		35.7	
Ø d2 (mm)		60.5	
L (mm)		64.5	
Torque wrench		50	
kg/u		0,117	
u		10	
Material		LATÓN NIQUELADO,POLIAMIDA 6	
IP		IP67	
Working temperature range (°C)		-25 / 105 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic