



### Description

40x30mm rail with a thickness of 1.5mm for medium loads in installations of cable trays, electrical conduits and other installations of heating pipes, A/C, fire protection systems, etc. With PG protection system. It has perforations on all 3 sides, increasing the possibilities of connecting supports and other items. Made of steel, available in various protection systems.

### Advantages

Together with the 3C Mounting Plate offering the opportunity to regulate the connection angle of the system, adapting to arches of tunnels, galleries and sloping walls

Available in PG and GC Protection Systems

CE conformity in accordance to the low voltage directive 2014 /35 /UE and the international product standard IEC 61537

Quick installation system. Thanks to the 3 side perforations allow a fast connection and screwing on the 3C Mounting Plate using M8x65 hexagonal screw.

Versatile installation system. We can connect different elements such as the 3C Mounting Plate for ceiling connection or as a lateral support for the wall, installing it laterally to the rail and increasing the stability and the load values of the set.

### Applications

Support for Cable Trays (rejiband®, pemsaband®, megaband®, among others) in ceiling installations in tunnels, service galleries, buildings or installations in industrial environments.

### Solutions



## Product data

|                                              |                    |                                       |                            |
|----------------------------------------------|--------------------|---------------------------------------|----------------------------|
| <b>ETIM 10</b>                               | EC000386           | <b>u</b>                              | 1                          |
| <b>Huella de CO2. GWP A1-A3 (kg CO2 eq.)</b> |                    | <b>Material</b>                       | Steel with surface coating |
| <b>Protection System</b>                     | PG                 | <b>Thickness (mm)</b>                 | 1.5                        |
| <b>Finish</b>                                | PG3, Pregalvanised | <b>Working temperature range (°C)</b> | -50 / 150 °C               |
| <b>Resistance Class</b>                      | Class 3            | <b>Fire resistance</b>                | A1 No combustible          |
| <b>Flange (mm)</b>                           | 30                 |                                       |                            |
| <b>Length (m)</b>                            | 1                  |                                       |                            |
| <b>kg/u</b>                                  | 1,030              |                                       |                            |

## Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



Product applications

□ □ □



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

