Cable tray Accessories

Right Reducer Pemsaband Vulcan



Description

Advantages

Plug-in connection system without additional couplers, only requiring the installation of the Coupler kit M 6 Pemsaband® Vulcan which allows saving costs in material and labor.

Applications

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Right Reducer Pemsaband Vulcan

Main technical characteristics

PG3, Pregalvanised, ZM High Resistance Alloy | 12, 18, 25, 50 | 75, 100, 150, 225, 300, 450, 600, 750, 900 | ETIM 10

Steel with surface coating | 20 J | IP44 | -50 / 150 °C | A1 No combustible

Product data

S	F	Class IEC 61537				REF
PG	PG3, Pregalvanised	Class 3	12	75	50	82005056
PG	PG3, Pregalvanised	Class 3	12	100	50	82005057
PG	PG3, Pregalvanised	Class 3	12	100	75	82005058
PG	PG3, Pregalvanised	Class 3	12	150	75	82005059
PG	PG3, Pregalvanised	Class 3	12	150	100	82005060
PG	PG3, Pregalvanised	Class 3	12	225	100	82005061
PG	PG3, Pregalvanised	Class 3	12	225	150	82005062
PG	PG3, Pregalvanised	Class 3	18	300	150	82005063
PG	PG3, Pregalvanised	Class 3	18	300	225	82005064
PG	PG3, Pregalvanised	Class 3	25	75	50	82005065
PG	PG3, Pregalvanised	Class 3	25	100	50	82005066
PG	PG3, Pregalvanised	Class 3	25	100	75	82005067
PG	PG3, Pregalvanised	Class 3	25	150	75	82005068
PG	PG3, Pregalvanised	Class 3	25	150	100	82005069
PG	PG3, Pregalvanised	Class 3	25	225	100	82005070
PG	PG3, Pregalvanised	Class 3	25	225	150	82005071
PG	PG3, Pregalvanised	Class 3	25	300	150	82005072
PG	PG3, Pregalvanised	Class 3	25	300	225	82005073
PG	PG3, Pregalvanised	Class 3	25	450	225	82005074
PG	PG3, Pregalvanised	Class 3	25	450	300	82005075
PG	PG3, Pregalvanised	Class 3	25	600	300	82005076
PG	PG3, Pregalvanised	Class 3	25	600	450	82005077
PG	PG3, Pregalvanised	Class 3	25	750	450	82005078
PG	PG3, Pregalvanised	Class 3	25	750	600	82005079
PG	PG3, Pregalvanised	Class 3	25	900	600	82005080
PG	PG3, Pregalvanised	Class 3	25	900	750	82005081
PG	PG3, Pregalvanised	Class 3	50	75	50	82005082
PG	PG3, Pregalvanised	Class 3	50	100	50	82005083
PG	PG3, Pregalvanised	Class 3	50	100	75	82005084
PG	PG3, Pregalvanised	Class 3	50	150	75	82005085
PG	PG3, Pregalvanised	Class 3	50	150	100	82005086
PG	PG3, Pregalvanised	Class 3	50	225	100	82005087
PG	PG3, Pregalvanised	Class 3	50	225	150	82005088
PG	PG3, Pregalvanised	Class 3	50	300	150	82005089
PG	PG3, Pregalvanised	Class 3	50	300	225	82005090

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Right Reducer Pemsaband Vulcan

S	F	Class IEC 61537				REF
PG	PG3, Pregalvanised	Class 3	50	450	225	82005091
PG	PG3, Pregalvanised	Class 3	50	450	300	82005092
PG	PG3, Pregalvanised	Class 3	50	600	300	82005093
PG	PG3, Pregalvanised	Class 3	50	600	450	82005094
PG	PG3, Pregalvanised	Class 3	50	750	450	82005095
PG	PG3, Pregalvanised	Class 3	50	750	600	82005096
PG	PG3, Pregalvanised	Class 3	50	900	600	82005097
PG	PG3, Pregalvanised	Class 3	50	900	750	82005098
AZ+	ZM High Resistance Alloy	Class 8	25	75	50	82005099
AZ+	ZM High Resistance Alloy	Class 8	25	100	50	82005100
AZ+	ZM High Resistance Alloy	Class 8	25	100	75	82005101
AZ+	ZM High Resistance Alloy	Class 8	25	150	75	82005102
AZ+	ZM High Resistance Alloy	Class 8	25	150	100	82005103
AZ+	ZM High Resistance Alloy	Class 8	25	225	100	82005104
AZ+	ZM High Resistance Alloy	Class 8	25	225	150	82005105
AZ+	ZM High Resistance Alloy	Class 8	25	300	150	82005106
AZ+	ZM High Resistance Alloy	Class 8	25	300	225	82005107
AZ+	ZM High Resistance Alloy	Class 8	25	450	225	82005108
AZ+	ZM High Resistance Alloy	Class 8	25	450	300	82005109
AZ+	ZM High Resistance Alloy	Class 8	25	600	300	82005110
AZ+	ZM High Resistance Alloy	Class 8	25	600	450	82005111
AZ+	ZM High Resistance Alloy	Class 8	25	750	450	82005112
AZ+	ZM High Resistance Alloy	Class 8	25	750	600	82005113
AZ+	ZM High Resistance Alloy	Class 8	25	900	600	82005114
AZ+	ZM High Resistance Alloy	Class 8	25	900	750	82005115
AZ+	ZM High Resistance Alloy	Class 8	50	75	50	82005116
AZ+	ZM High Resistance Alloy	Class 8	50	100	50	82005117
AZ+	ZM High Resistance Alloy	Class 8	50	100	75	82005118
AZ+	ZM High Resistance Alloy	Class 8	50	150	75	82005119
AZ+	ZM High Resistance Alloy	Class 8	50	150	100	82005120
AZ+	ZM High Resistance Alloy	Class 8	50	225	100	82005121
AZ+	ZM High Resistance Alloy	Class 8	50	225	150	82005122
AZ+	ZM High Resistance Alloy	Class 8	50	300	150	82005123
AZ+	ZM High Resistance Alloy	Class 8	50	300	225	82005124
AZ+	ZM High Resistance Alloy	Class 8	50	450	225	82005125
AZ+	ZM High Resistance Alloy	Class 8	50	450	300	82005126
AZ+	ZM High Resistance Alloy	Class 8	50	600	300	82005127
AZ+	ZM High Resistance Alloy	Class 8	50	600	450	82005128
AZ+	ZM High Resistance Alloy	Class 8	50	750	450	82005129
AZ+	ZM High Resistance Alloy	Class 8	50	750	600	82005130
AZ+	ZM High Resistance Alloy	Class 8	50	900	600	82005131

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Right Reducer Pemsaband Vulcan

Ⓢ	Ⓕ	Class IEC 61537				REF
AZ+	ZM High Resistance Alloy	Class 8	50	900	750	82005132

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."