

Right Reducer Pemsaband Vulcan (Ref: 82005117)



Description

Advantages

Applications

Solutions



Product data

ETIM 10		Material	Steel with surface coating
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		Impact Strength (J)	20 J
Protection System	AZ+	IP	IP44
Finish	ZM High Resistance Alloy	Working temperature range (°C)	-50 / 150 °C
Resistance Class	Class 8	Fire resistance	A1 No combustible
Flange (mm)	50		
Width (mm)	100		
Reduce to:	50		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic