


Left Reducer Pemsaband Vulcan (Ref: 82005184)



Description

Advantages

Applications

Solutions



Product data	
ETIM 10	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	
Protection System	AZ+
Finish	ZM High Resistance Alloy
Resistance Class	Class 8
Flange (mm)	25
Width (mm)	300
Reduce to:	225

Material	Steel with surface coating
Impact Strength (J)	20 J
IP	IP44
Working temperature range (°C)	-50 / 150 °C
Fire resistance	A1 No combustible



Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass



Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic